

NEW

RYCO
COMMERCIAL

RCK400 CATCH CAN

for Isuzu Light Diesel Trucks

The workhorse of the Japanese Truck market is the **ISUZU N Series 4HK1**.

The problem is the N Series were not fitted with a factory PCV filter, overtime the oil vapour "blow-by" oil soaks engine air intake components, cooler pipes, turbocharger, exhaust and EGR valves this causes carbon build up, this results in loss of power and fuel efficiency.



The solution is fitting a Ryco RCK400 catch can kit. By plumbing in a PCV filter you now collect the "blow by" and greatly reduce your maintenance cost, extend the life of the engine and protect your investment.



The RCK400 kit includes everything to do the job and can be **installed in 30 minutes**.

View on

 youtube.com/RycofiltersAUS

PRODUCT DATA SHEET

RCK400 CATCH CAN KIT FOR ISUZU LIGHT DIESEL TRUCKS

A Ryco Crankcase filter assembly prevents crankcase gases from contaminating engine air intake components, reducing efficiency and leading to expensive maintenance.

The rate at which the catchcan will capture contaminants and the 300ml sump require draining will vary greatly depending on the age and condition of the engine.

PRODUCT SNAPSHOT

Suitable for:

- Isuzu N Series with 4HK1 engine, 2008 to 2018

Kit includes:



RCC351 crankcase assembly



RCC151F replacement element (fitted in Catchcan)



Straight hose joiner x 2
25 mm ID hose clamps x 2



Specifically designed PCV hoses x 2
Additional length of PCV hose (1000mm) x 1



M8x35mm (High Strength) Bolts,
Flange Nuts, Washers & Zip Ties



Universal e-coated mounting bracket

- ✓ Specialized high efficiency coalescing filter media
- ✓ Provides optimal oil separation
- ✓ Removes other contaminants from the crank case emissions down to 1 micron
- ✓ Keeps the EGR valve clean
- ✓ Designed and engineered by Ryco in Australia



Replacement Element

RCC151F

Interchangeable with: LC7201x

The element is made from specialized high efficiency coalescing filter media.

The element is not washable or reusable.



- 1 Flexible orientation outlet port (size 1")
- 2 High efficiency oil vapour coalescing filter media
- 3 Integrated by pass valve (opens @ +5kPa)
- 4 300 ml storage sump
- 5 Flexible orientation inlet port
- 6 Quick release universal mounting bracket design
- 7 Easy to use drain tap (size 8mm).

Available from your Ryco Filter stockist today.

Australia: Telephone 1800 804 541 or www.rycofilters.com.au
New Zealand: Telephone 0800 838 222 or www.ryco.co.nz

RYCO
FILTERS